



Swimming pool control panel for 1 Single-phase Skimmer pump

- Waterproof box in self-extinguishing resin IP65
- 12 modules with transparent door;
- Voltage input 1 ~ 50/60Hz 230V ±10%
- Earthleakage 30 mA ;
- Auto-Off-Manual **PUMP** operation;
- N°1 green led for power supply;
- N°1 green led for **PUMP** operating;
- N°1 red led for alarm **PUMP** in overload protection;
- N°1 red led for alarm **FILTER BLOCKED** (stop of the pump);
- Adjustable **PUMP** overload protection from 0,5 to 3 Hp;
- **Pump** protection fuse;
- **FILTRATION** daily timer;
- Automatic magnetic circuit breaker 16 A for **SPOTLIGHT**;



Swimming pool control panel for 1 Three-phase Skimmer pump

- Waterproof box in self-extinguishing resin IP55
- 24 modules with transparent door;
- Earthleakage 30 mA ;
- Voltage input 3 ~ 50/60Hz 400V ±10% ;
- Auto-Off-Manual **PUMP** operation;
- N°1 green led for power supply;
- N°1 green led for **PUMP** operating;
- N°1 red led for alarm **PUMP** in overload protection;
- N°1 red led for alarm **FILTER BLOCKED** (stop of the pump);
- Adjustable **PUMP** overload protection from 0,5 to 7,5 Hp;
- **Pump** protection fuse;
- **FILTRATION** daily timer;
- Automatic magnetic circuit breaker 16 A for **SPOTLIGHT**;

The panels are predisposed for Deck Level Kit

- Very low voltage input for minimum level in compensation tank alarm signalling;
- Red led for minimum water level alarm
- Alarm output with exchangeable contact 5A 250V (for **Deck Level kit**);

Code	Models	(A) max	Dimension (mm)	Weight (kg)
	Single-phase			
001.71	MODULPoolStar-M	2,0 ÷ 18,0	312 x 252 x 145	2,2
	Three-phase			
001.73	MODULPoolStar-T	2,0 ÷ 11,0	312 x 376 x 145	3,7



Optional

Code	Models	(VA) Max	Dimension (mm)	Weight (Kg)
001.44	Pool L01 (230V 1F)	1x350VA	340 x 240 x 170	6,0
001.45	Pool L02 (230V 1F)	2x350VA	340 x 240 x 170	8,0
001.51	Kit Sfiro			1,5
001.51	SL-1 sonda di livello			0,2

